

GulfSea Hydraulic HVI Plus 150	Page:	1/9
2019-11-18	Revision:	2019-11-18
	SDS-ID:	HK-EN/1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING1.1. Product identifierProduct name:GulfSea Hydraulic HVI Plus 150Container size:-1.2. Relevant identified uses of the substance or mixture and uses advised againstApplication:Hydraulic oil.1.3. Details of the supplier of the safety data sheetSupplier:Gulf Marine Pte. Ltd.
37 Tuas Road,
Singapore 638503
Tel: +65 6592 0120
Email: sds@gulf-marine.com

1.4. Emergency telephone number

Emergency telephone: Tel: +65 6592 0120

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS: Not classified.

2.2. Label elements

Safety data sheet available on request.

2.3. Other hazards

<u>PBT/vPvB:</u> Not applicable.

Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Only classified substances above threshold limits are shown.

GHS:

Other:

<u>%:</u>	CAS-No.:	<u>EC No.:</u>	<u>REACH Reg.</u> <u>No:</u>	Chemical name:	Hazard classification:	<u>Notes:</u>
80-95	64742-64-7	265-157-1	-	Distillates (petroleum), hydrotreated heavy paraffinic	Asp. Tox. 1;H304	



Product name:	GulfSea Hydraulic HVI Plus 150	Page:	2/9
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

Reference:

The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:	Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.	
<u>Skin contact:</u>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.	
Eye contact:	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.	
Ingestion:	Rinse mouth with water. Drink 1-2 glasses of water. Do not induce vomiting. Get medical attention.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects:	Defatting, drying and cracking of skin.	
4.3. Indication of any immediate medical attention and special treatment needed		

<u>Medical attention/treatments:</u> Treat symptomatically. If swallowed, especially in large quantities: Get medical attention.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media:	Extinguish with foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fro	om the substance or mixture
<u>Specific hazards:</u>	When heated and in case of fire, harmful vapours/gases may be formed. Fire in closed areas should only be extinguished by trained personnel.
5.3. Advice for firefighters	
Protective equipment for fire- fighters:	Evacuate personnel from immediate vicinity. Wear self-contained breathing apparatus and full personal protection.



Product name:	GulfSea Hydraulic HVI Plus 150	Page:	3/9
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

, <u>-</u> , <u>-</u> , <u>-</u> ,,,,,,,	
Personal precautions:	If leakage cannot be stopped, evacuate area. Mark the spillage. Avoid inhalation of oil mist and contact with skin and eyes. Keep public away from danger area. In case of spills, beware of slippery floors and surfaces.
Protective equipment:	Put on protective equipment before entering danger area.
6.2. Environmental precautio	<u>ns</u>
Environmental precautions:	Prevent spillage entering a watercourse or sewer, contaminating soil or vegetation. If this is not possible notify police and appropriate authorities immediately.
6.3. Methods and material for	r containment and cleaning up
Methods for cleaning up:	Stop leak if possible without risk. Soak up with inert absorbent material. Large Spillages: Stop leak if possible without risk. Dam and absorb spillages with sand, earth or other non-combustible material.
6.4. Reference to other section	ons
Reference:	For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Observe good chemical hygiene practices. Avoid inhalation of oil mist and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Wash hands before breaks and before smoking, eating or drinking.
Technical measures:	Use work methods which minimise oil mist production. Do not smoke or use open fire or other sources of ignition.
Technical precautions:	When working with heated oil, mechanical ventilation may be required.
7.2. Conditions for safe storag	e, including any incompatibilities
Technical measures for safe storage:	Store in tightly closed original container in a well-ventilated place. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage. Ensure that the container is undamaged and has a proper label. Use appropriate containment to avoid environmental contamination.
Storage conditions:	Store in tightly closed original container in a well-ventilated place. Protect from heat and direct sunlight.
7.3. Specific end use(s)	
<u>Specific use(s):</u>	Lubricant.



GulfSea Hydraulic HVI Plus 150	Page:	4/9
2019-11-18	Revision:	2019-11-18
	SDS-ID:	HK-EN/1.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

CAS-No.:	Chemical name:	<u>As:</u>	Exposure limits:	<u>Type:</u>	Notes:	References:
-	Oil mist, -mineral	-	5 mg/m3	PEL (Long Term)	-	
		-	10 mg/m3	PEL (Short Term)	-	
DNEL/PNEC	:	DNEL: Not available PNEC: Not available				

8.2. Exposure controls

Engineering measures:	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and oil mist.
Respiratory equipment:	In case of inadequate ventilation use suitable respirator. Use respiratory equipment with gas filter, type A1. If the product is heated under manual handling, use suitable mask with filter A1P2 or A2P2.
Hand protection:	Nitrile gloves are recommended. If signs of wear and tear are noticed then the gloves should be replaced. The most suitable glove must be chosen in collaboration with the gloves supplier, who can inform about the breakthrough time of the glove material.
Eye protection:	Wear approved, tight fitting safety glasses where splashing is probable.
Skin protection:	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<u>Hygiene measures:</u>	Wash hands after handling. Observe good chemical hygiene practices. Wash contaminated clothing before reuse. When using do not eat, drink or smoke. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.



Product No.:

SAFETY DATA SHEET

GulfSea Hydraulic HVI Plus 150 2019-11-18

 Page:
 5/9

 Revision:
 2019-11-18

 SDS-ID:
 HK-EN/1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic phy	sical and chemical properties
Appearance:	Oily liquid
<u>Colour:</u>	Clear to yellow.
<u>Odour:</u>	Characteristic.
Odour threshold:	Not available.
<u>рН:</u>	Not available.
<u>Pour point (°C):</u>	-30°C
Boiling point:	Not available.
Flash point:	OC (Open cup). 248°C [ASTM D92.]
Evaporation rate:	Not available.
<u>Flammability (solid, gas):</u>	Not applicable.
Explosion limits:	Not available.
Vapour pressure:	<0.01 kPa (20°C)
<u>Vapour density:</u>	Not available.
Relative density:	~ 0.87
Solubility:	Soluble in: Organic solvents. Insoluble in water.
Partition coefficient (n-octanol/water):	Not available.
<u>Auto-ignition</u> temperature (°C):	>300°C
Decomposition temperature (°C):	>300°C
<u>Viscosity:</u>	147.2 mm²/s (40 °C)
	19.5 mm²/s (100°C)
Explosive properties:	Not applicable.
Oxidising properties:	Not applicable.
9.2. Other information	
Other data:	Not available.



Product No.:

SAFETY DATA SHEET

GulfSea Hydraulic HVI Plus 150 Page: 2019-11-18 Revision: SDS-ID:

6/9 2019-11-18 HK-EN/1.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not reactive. Reactivity: 10.2. Chemical stability Stability: Stable under normal temperature conditions. 10.3. Possibility of hazardous reactions None under normal conditions. Hazardous reactions: 10.4. Conditions to avoid Conditions/materials to avoid: Heat, sparks, flames. 10.5. Incompatible materials Incompatible materials: Strong oxidizing substances. 10.6. Hazardous decomposition products Hazardous decomposition Hazardous polymerisation will not occur.

products:



GulfSea Hydraulic HVI Plus 150	Page:	7/9
2019-11-18	Revision:	2019-11-18
	SDS-ID:	HK-EN/1.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects				
Inhalation:	Inhalation of oil mist or vapours formed during heating of the product may irritate the respiratory system and provoke throat irritation and coughing.			
Skin contact:	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.			
Eye contact:	May cause temporary eye irritation.			
Ingestion:	Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.			
Specific effects:	Used oil may contain harmful contaminants.			
Toxicological data:	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil-unspecified			
	Acute toxicity: LC50 (inhalation, rat, 4h): 5.53 mg/l LD50 (dermal, rabbit): >5000 mg/kg LD50 (oral, rat): >5000 mg/kg Skin Corrosion/Irritation: Erythema\eschar score: 0.17, Rabbit, Duration: 72 hours, Observation: 7 days Oedema score: 0, Rabbit, Duration: 72 hours, Observation: 7 days Iritis score: 0, Rabbit, Duration: 48 hours, Observation: 72 hours Conjunctivitis score: 0.33 Rabbit, Duration: 48 hours, Observation: 72 hours Skin sensitisation: Not a skin sensitiser (guinea pig). Mutagenicity: Negative. Carcinogenicity: Negative. Reproductive Toxicity: Negative.			
	Teratogenicity: Negative.			
	STOT - Single exposure:, Not available.			
	STOT - Repeated exposure:, Not available.			
	Aspiration hazard: Aspiration toxicity Cat 1			



Product name:	GulfSea Hydraulic HVI Plus 150	Page:	8/9
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Not harmful to aquatic organisms. Expected LC/EC50 value > 100 mg/l

12.2. Persistence and degradability

<u>Degradability:</u> Potentially degradable, but will persist in the environment for long periods.

12.3. Bioaccumulative potential

Bioaccumulative potential: LogPow: >3

12.4. Mobility in soil

Mobility: Spillages may penetrate the soil causing ground water contamination.

12.5. Results of PBT and vPvB assessment

PBT/vPvB:

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Other adverse effects: Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste is classified as hazardous waste. Dispose of waste and residues in accordance with local authority requirements.

<u>Contaminated packaging:</u> Disposal through approved facilities is recommended.

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

<u>14.1. UN number</u>			
<u>UN-No:</u>	Not regulated.		
14.2. UN proper shipping name			
Proper Shipping Name:	Not regulated.		
14.3. Transport hazard class(es)			
<u>Class:</u>	Not regulated.		
14.4. Packing group			
<u>PG:</u>	Not regulated.		
14.5. Environmental hazards			
Marine pollutant:	Not regulated.		
Environmentally Hazardous Substance:	Not regulated.		
14.6. Special precautions for user			
Special precautions:	Not regulated.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			
Transport in bulk:	Not regulated.		



GulfSea Hydraulic HVI Plus 150	Page:	9/9
2019-11-18	Revision:	2019-11-18
	SDS-ID:	HK-EN/1.0

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation:Singapore Standard SS 586: Part 2 : 2014; Globally harmonised system of
classification and labelling of chemicals - Singapore's adaptations.
Singapore Standard SS 586: Part 3 : 2014; Preparation of safety data sheets
(SDS).
Guidelines on prevention and control of chemical hazard.

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

Wording of H-statements:

H304

May be fatal if swallowed and enters airways.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature.