

SAFETY DATA SHEET

 Product name:
 GulfSea Synth Gear Oil PG 220
 Page:
 1/10

 Supersedes date:
 2019-11-18
 Revision:
 2019-11-18

 Product No.:
 SDS-ID:
 HK-EN/1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1.Product identifier

Product name: GulfSea Synth Gear Oil PG 220

Container size: -

1.2.Relevant identified uses of the substance or mixture and uses advised against

Application: Gear oil.

1.3.Details of the supplier of the safety data sheet

Supplier: Gulf Marine Pte. Ltd.

37 Tuas Road, Singapore 638503 Tel: +65 6592 0120

Email: sds@gulf-marine.com

1.4.Emergency telephone number

Emergency telephone: Tel: +65 6592 0120

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS: Not classified.

2.2.Label elements

The substance/mixture does not meet the criteria for classification and labelling.

2.3.Other hazards

PBT/vPvB: Not applicable.

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation,

eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Mineral oil and additives (DMSO < 3% (IP 346)

No classified ingredients, or those having occupational exposure limits, present above the levels of disclosure.

SAFETY DATA SHEET

Product name:GulfSea Synth Gear Oil PG 220Page:2/10Supersedes date:2019-11-18Revision:2019-11-18Product No.:SDS-ID:HK-EN/1.0

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation

or coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water. Get

medical attention if any discomfort continues.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any

contact lenses and open eyelids widely. If irritation persists: Seek medical

attention and bring along these instructions.

Ingestion: Rinse mouth with water. Drink 1-2 glasses of water. Do not induce vomiting.

Get medical attention.

4.2.Most important symptoms and effects, both acute and delayed

<u>Symptoms/effects:</u> Defatting, drying and cracking of skin.

4.3.Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically. If swallowed, especially in large quantities: Get medical

attention.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog. Cool

containers exposed to heat with water spray and remove container, if no risk

is involved.

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards: When heated and in case of fire, harmful vapours/gases may be formed. Fire in

closed areas should only be extinguished by trained personnel.

5.3. Advice for firefighters

<u>Protective equipment for</u> Evacuate personnel from immediate vicinity. Wear self-contained breathing

fire-fighters: apparatus and full personal protection.

Marine

SAFETY DATA SHEET

3/10 Product name: GulfSea Synth Gear Oil PG 220 Page: Supersedes date: 2019-11-18 Revision: 2019-11-18 Product No.: SDS-ID: HK-EN/1.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

If leakage cannot be stopped, evacuate area. Mark the spillage. Avoid inhalation Personal precautions:

of oil mist and contact with skin and eyes. Keep public away from danger area. In

case of spills, beware of slippery floors and surfaces.

Put on protective equipment before entering danger area. Protective equipment:

6.2. Environmental precautions

Environmental Prevent spillage entering a watercourse or sewer, contaminating soil or precautions:

vegetation. If this is not possible notify police and appropriate authorities

immediately.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Soak up with inert absorbent material. Methods for cleaning up:

Large Spillages: Stop leak if possible without risk. Dam and absorb spillages with

sand, earth or other non-combustible material.

6.4.Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13. Reference:

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid inhalation of oil mist and

> contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Wash hands before breaks and before smoking, eating or

drinking.

Technical measures: Use work methods which minimise oil mist production. Do not smoke or use

open fire or other sources of ignition.

When working with heated oil, mechanical ventilation may be required. Technical precautions:

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe

storage:

Store in tightly closed original container in a well-ventilated place. Containers, which are opened, must be carefully resealed and kept upright to prevent

leakage. Ensure that the container is undamaged and has a proper label. Use

appropriate containment to avoid environmental contamination.

Store in tightly closed original container in a well-ventilated place. Protect Storage conditions:

from heat and direct sunlight.

7.3. Specific end use(s)

Specific use(s): Lubricant.

SAFETY DATA SHEET

Product name:GulfSea Synth Gear Oil PG 220Page:4/10Supersedes date:2019-11-18Revision:2019-11-18Product No.:SDS-ID:HK-EN/1.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

CAS-No.: Chemical name: As: Exposure limits: Type: Notes: References:

- Oil mist, -mineral - 5 mg/m3 PEL (Long -

Term)

10 mg/m3 PEL (Short

Term)

DNEL/PNEC: DNEL: Not available.

PNEC: Not available.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and

minimize the risk of inhalation of vapours and oil mist.

Respiratory equipment: In case of inadequate ventilation use suitable respirator. Use respiratory

equipment with gas filter, type A1. If the product is heated under manual

handling, use suitable mask with filter A1P2 or A2P2.

Hand protection: Nitrile gloves are recommended. If signs of wear and tear are noticed then the

gloves should be replaced. The most suitable glove must be chosen in

collaboration with the gloves supplier, who can inform about the breakthrough

time of the glove material.

Eye protection: Wear approved, tight fitting safety glasses where splashing is probable.

Skin protection: Wear appropriate clothing to prevent repeated or prolonged skin contact.

<u>Hygiene measures:</u> Wash hands after handling. Observe good chemical hygiene practices. Wash

contaminated clothing before reuse. When using do not eat, drink or smoke. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not

put rags moistened with oil into pockets.

GulfMarine

SAFETY DATA SHEET

 Product name:
 GulfSea Synth Gear Oil PG 220
 Page:
 5/10

 Supersedes date:
 2019-11-18
 Revision:
 2019-11-18

 Product No.:
 SDS-ID:
 HK-EN/1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance: Clear liquid.

Colour: Yellow.

Odour: Mild.

Odour threshold:Not available.pH:Not applicable.Melting point / freezing point:Not available.Boiling point:Not available.Flash point:260°C

Evaporation rate:

Flammability (solid, gas):

Explosion limits:

Vapour pressure:

Vapour density:

Relative density:

Not available.

Not available.

Not available.

Not available.

Not available.

<u>Solubility:</u> Not available. <u>Partition coefficient</u> Not available.

(n-octanol/water):

<u>Auto-ignition</u> Not available.

temperature (°C):

<u>Decomposition</u> Not available.

temperature (°C):

Viscosity: 234.0 mm²/s (40 °C)

Explosive properties: Not applicable.

Oxidising properties: Not applicable.

9.2. Other information

Pour point(°C): -32°C



SAFETY DATA SHEET

Product name:GulfSea Synth Gear Oil PG 220Page:6/10Supersedes date:2019-11-18Revision:2019-11-18Product No.:SDS-ID:HK-EN/1.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

<u>Hazardous reactions:</u> None under normal conditions.

10.4. Conditions to avoid

Conditions/materials to avoid: Heat, sparks, flames. Moisture.

10.5. Incompatible materials

<u>Incompatible materials:</u> Strong oxidizing and reducing substances.

10.6. Hazardous decomposition products

<u>Hazardous decomposition</u> Hazardous polymerisation will not occur.

products:

SAFETY DATA SHEET

Product name:GulfSea Synth Gear Oil PG 220Page:7/10Supersedes date:2019-11-18Revision:2019-11-18Product No.:SDS-ID:HK-EN/1.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral):

Acute Toxicity (Dermal):

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation:

Based on available data, the classification criteria are not met.

<u>Germ cell mutagenicity:</u>

<u>Carcinogenicity:</u>

Based on available data, the classification criteria are not met.

<u>Reproductive Toxicity:</u>

Based on available data, the classification criteria are not met.

<u>Based on available data, the classification criteria are not met.</u>

<u>Based on available data, the classification criteria are not met.</u>

<u>Based on available data, the classification criteria are not met.</u>

<u>Based on available data, the classification criteria are not met.</u>

<u>Based on available data, the classification criteria are not met.</u>

Aspiration hazard: Based on available data, the classification criteria are not met.

<u>Inhalation:</u> Inhalation of oil mist or vapours formed during heating of the product may irritate

the respiratory system and provoke throat irritation and coughing.

Skin contact: Prolonged or repeated contact with used oil may cause serious skin diseases,

such as dermatitis.

<u>Eye contact:</u> May cause temporary eye irritation.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may

cause severe and potentially fatal chemical pneumonitis.

Specific effects: Used oil may contain harmful contaminants.

<u>Toxicological data:</u> Skin sensitisation: No information available.

Mutagenicity: No information available.

Carcinogenicity: No information available.

Reproductive Toxicity: No information available.

Teratogenicity: No information available.

STOT - Single exposure:, Not available.

STOT - Repeated exposure:, Not available.

Aspiration hazard: No information available.

SAFETY DATA SHEET

 Product name:
 GulfSea Synth Gear Oil PG
 Page:
 8/10

 Supersedes date:
 220
 Revision:
 2019-11-18

 Product No.:
 2019-11-18
 SDS-ID:
 HK-EN/1.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Not classified as dangerous to the environment.

12.2. Persistence and degradability

Degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: Spillages may penetrate the soil causing ground water contamination.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: No data available.

12.6. Other adverse effects

Other adverse effects: Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste is classified as hazardous waste. Dispose of waste and residues in accordance with local authority requirements.

Waste from residues: EWC-code: 13 02 05

<u>Contaminated packaging:</u> Disposal through approved facilities is recommended.

SAFETY DATA SHEET

 Product name:
 GulfSea Synth Gear Oil PG 220
 Page:
 9/10

 Supersedes date:
 2019-11-18
 Revision:
 2019-11-18

 Product No.:
 SDS-ID:
 HK-EN/1.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA).

14.1. UN number

UN-No: Not regulated.

14.2. UN proper shipping name

<u>Proper Shipping Name:</u> Not regulated.

14.3. Transport hazard class(es)

<u>Class:</u> Not regulated.

14.4.Packing group

PG: Not regulated.

14.5.Environmental hazards

Marine pollutant: Not regulated. Environmentally Hazardous Not regulated.

Substance:

14.6.Special precautions for user

Special precautions: Not regulated.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

<u>Transport in bulk:</u> Not regulated.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation:

Singapore Standard SS 586: Part 2 : 2014; Globally harmonised system of

classification and labelling of chemicals - Singapore's adaptations.

Singapore Standard SS 586: Part 3: 2014; Preparation of safety data sheets

(SDS).

Guidelines on prevention and control of chemical hazard.



SAFETY DATA SHEET

Product name:GulfSea Synth Gear Oil PG 220Page:10/10Supersedes date:2019-11-18Revision:2019-11-18Product No.:SDS-ID:HK-EN/1.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

Wording of H-statements:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H373G May cause damage to organs (gastro-intestinal tract, liver, immune

system) through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.
 H412
 Harmful to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature.