

GulfSea Hydraulic SHVI 15	Page:	1/11
2020-11-07	Revision:	2020-11-07
	SDS-ID:	HK-EN/2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: GulfSea Hydraulic SHVI 15

Container size:

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Hydraulic oil.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Gulf Marine Pte. Ltd. 37 Tuas Road, Singapore 638503 Tel: +65 6592 0120 Email: sds@gulf-marine.com

1.4. Emergency telephone number

Emergency telephone: Tel: +65 6592 0120

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS:Aspiration hazard Cat 1Flammable liquids Cat 4; Skin irritation Cat 2

2.2. Label elements

	Danger
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H411	Toxic to aquatic life with long lasting effects.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protec-tion/ face protection/ hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/ attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P503	Store in a well-ventilated place.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.
2.3. Other hazards	
Other:	Prolonged or repeated contact with skin may cause redness, itching, irritation,
	eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

Product name:	GulfSea Hydraulic SHVI 15	Page:	2/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Only classified substances above threshold limits or substances with an exposure limit are shown.

GHS:

<u>%:</u>	CAS-No.:	<u>EC No.:</u>	<u>REACH Reg.</u> <u>No:</u>	Chemical name:	Hazard classification:	<u>Notes:</u>
50-70	64742-53-6	265-156-6	-	Distillates (petroleum), hydrotreated light naphthenic	Asp. Tox. 1;H304	
15-20	64742-46-7	265-148-2	-	Distillates (petroleum), hydrotreated middle; Gasoil- unspecified	Asp. Tox. 1;H304	
0.25-1	68937-40-6	273-065-8	-	Phenol, isobutylenated, phosphate [Triphenyl phosphate > 25%]	Asp. Tox. 1;H304	
0.25-1	68937-40-6	204-881-4	-	2,6-di-tert-butyl-p-cresol		
Notes:		L:	DMSO < 3% (IP	346)		
Referer	nce:	Th	e full text for all h	nazard statements is display	ed in section 16.	

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures			
Inhalation:	Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.		
Skin contact:	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.		
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.		
Ingestion:	DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration hazard. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Rinse mouth with water. If unconcious: Loosen tight fitting clothes and place in recovery position.		
4.2. Most important symptoms	s and effects, both acute and delayed		
Symptoms/effects:	Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Defatting, drying and cracking of skin.		
4.3. Indication of any immediate medical attention and special treatment needed			
Medical attention/treatments:	Treat symptomatically. If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.		

Product name:	GulfSea Hydraulic SHVI 15	Page:	3/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media:	Extinguish with foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.	
	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards:	When heated and in case of fire, harmful vapours/gases may be formed. Fire in closed areas should only be extinguished by trained personnel.	
5.3. Advice for firefighters		
Protective equipment for fire- fighters:	Evacuate personnel from immediate vicinity. Self-contained breathing apparatus. Wear full protective clothing.	

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

	, ,, ,, , ,, , ,, , , , , , , , , , , , , , , , , , , ,
Personal precautions:	If leakage cannot be stopped, evacuate area. Mark the spillage. Avoid inhalation of oil mist and contact with skin and eyes. Keep public away from danger area. In case of spills, beware of slippery floors and surfaces.
Protective equipment:	Put on protective equipment before entering danger area.
6.2. Environmental precautio	ns
Environmental precautions:	Prevent spillage entering a watercourse or sewer, contaminating soil or vegetation. If this is not possible notify police and appropriate authorities immediately.
6.3. Methods and material fo	r containment and cleaning up
Methods for cleaning up:	Absorb with sand or other inert absorbent. Large Spillages: Stop leak if possible without risk. Dam and absorb spillages with sand, earth or other non-combustible material.
6.4. Reference to other section	ons

0.4. Reference to other se

<u>Reference:</u> For personal protection, see section 8. For waste disposal, see section 13.

Product name:	GulfSea Hydraulic SHVI 15	Page:	4/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe hand	lling
Safe handling advice:	Observe good chemical hygiene practices. Avoid inhalation of oil mist and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Wash hands before breaks and before smoking, eating or drinking.
Technical measures:	Use work methods which minimise oil mist production. Do not smoke or use open fire or other sources of ignition.
Technical precautions:	When working with heated oil, mechanical ventilation may be required.
7.2. Conditions for safe storage	ge, including any incompatibilities
Technical measures for safe storage:	Store in tightly closed original container in a well-ventilated place. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage. Ensure that the container is undamaged and has a proper label. Use appropriate containment to avoid environmental contamination.
Storage conditions:	Store in tightly closed original container in a well-ventilated place. Protect from heat and direct sunlight.
7.3. Specific end use(s)	
<u>Specific use(s):</u>	Lubricant.

Product name:	GulfSea Hydraulic SHVI 15	Page:	5/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

CAS-No.:	Chemical name:	<u>As:</u>	Exposure limits:	<u>Type:</u>	Notes:	References:
-	Oil mist, -mineral	-	5 mg/m3	PEL (Long Term)	-	SG
		-	10 mg/m3	PEL (Short Term)	-	
DNEL/PNEC	:	DNEL: Not availabl PNEC: Not availabl	-			

8.2. Exposure controls

Engineering measures:	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and oil mist.
Respiratory equipment:	In case of inadequate ventilation use suitable respirator. Use respiratory equipment with gas filter, type A1. If the product is heated under manual handling, use suitable mask with filter A1P2 or A2P2.
Hand protection:	Nitrile gloves are recommended. If signs of wear and tear are noticed then the gloves should be replaced. The most suitable glove must be chosen in collaboration with the gloves supplier, who can inform about the breakthrough time of the glove material.
Eye protection:	Wear approved, tight fitting safety glasses where splashing is probable.
Skin protection:	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<u>Hygiene measures:</u>	Wash hands after handling. Observe good chemical hygiene practices. Wash contaminated clothing before reuse. When using do not eat, drink or smoke. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Product name:	GulfSea Hydraulic SHVI 15	Page:	6/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Liquid. Appearance: Red. Colour: Odour: Aromatic. Odour threshold: Not available. <u>pH:</u> Not applicable. Melting point / freezing point: Not available. Boiling point: Not available. > 93.3°C (ASTM D93) Flash point: Evaporation rate: Not available.

Flammability (solid, gas):	Not applicable.
Explosion limits:	Not available.
Vapour pressure:	Not available.
Vapour density:	Not available.
Relative density:	0.87
<u>Solubility:</u>	Soluble in: Organic solvents. Insoluble in water.
Partition coefficient (n-octanol/water):	Not available.
<u>Auto-ignition</u> temperature (°C):	Not available.
Decomposition temperature (°C):	Not available.
<u>Viscosity:</u>	13.9 mm²/s (40°C)
Explosive properties:	Not applicable.
Oxidising properties:	Not applicable.
9.2. Other information	
<u>Other data:</u>	Pour point (°C): -60

Product name:	GulfSea Hydraulic SHVI 15	Page:	7/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not reactive. Reactivity: 10.2. Chemical stability Stability: Stable under normal temperature conditions. 10.3. Possibility of hazardous reactions None under normal conditions. Hazardous reactions: 10.4. Conditions to avoid Conditions/materials to avoid: Heat, sparks, flames. 10.5. Incompatible materials Incompatible materials: Strong oxidizing substances. 10.6. Hazardous decomposition products Hazardous decomposition Hazardous polymerisation will not occur. products:

Product name:	GulfSea Hydraulic SHVI 15	Page:	8/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicologi	ical effects
Acute Toxicity (Oral):	Based on available data, the classification criteria are not met.
Acute Toxicity (Dermal):	Based on available data, the classification criteria are not met.
Acute Toxicity (Inhalation):	Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation:	Based on available data, the classification criteria are not met.
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.
<u>Respiratory or skin</u> sensitisation:	Based on available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	Based on available data, the classification criteria are not met.
STOT - Single exposure:	Based on available data, the classification criteria are not met.
STOT - Repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	May be fatal if swallowed and enters airways.
Inhalation:	Inhalation of oil mist or vapours formed during heating of the product may irritate the respiratory system and provoke throat irritation and coughing.
Skin contact:	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.
Eye contact:	May cause temporary eye irritation.
Ingestion:	Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.
Specific effects:	Used oil may contain harmful contaminants.
Toxicological data:	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil- unspecifiedDistillates (petroleum), hydrotreated light naphthenicDistillates (petroleum), solvent-dewaxed light paraffinic; Baseoil-unspecifiedDistillates (petroleum), solvent-dewaxed light paraffinic; Baseoil-unspecifiedDistillates (petroleum), hydrotreated light naphthenic

Product name:	GulfSea Hydraulic SHVI 15	Page:	9/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 12: ECOLOGICAL INFORMATION 12.1. Toxicity

Ecotoxicity:	Not harmful to aquatic organisms. Expected LC/EC50 value > 100 mg/l	
12.2. Persistence and degrad	ability	
<u>Degradability:</u>	Potentially degradable, but will persist in the environment for long periods.	
12.3. Bioaccumulative potenti	<u>al</u>	
Bioaccumulative potential:	LogPow: >3: Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil-unspecified	
12.4. Mobility in soil		
<u>Mobility:</u>	Spillages may penetrate the soil causing ground water contamination.	
12.5. Results of PBT and vPvB assessment		
<u>PBT/vPvB:</u>	Not applicable.	
12.6. Other adverse effects		
Other adverse effects:	Not known.	
SECTION 13: DISPOSAL CONSIDERATIONS		

13.1. Waste treatment methods

Waste is classified as hazardous waste. Dispose of waste and residues in accordance with local authority requirements.

Waste from residues: EWC-code: 13 01 10

<u>Contaminated packaging:</u> Disposal through approved facilities is recommended.

Product name:	GulfSea Hydraulic SHVI 15	Page:	10/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 14: TRANSPORT INFORMATION

IATA-DGR	
<u>UN-No:</u>	: UN 3082.
Proper Shipping Name	: Environmentally hazardous substance, liquid, n.o.s. (Distillates (petroleum), hydrotreated middle, Phenol, isobu-tylenated, phosphate [Triphenyl phosphate > 25%])
<u>Class:</u>	: 9
Packing group:	: 111
Packing instruction (cargo aircraft)	: 964
Packing instruction	: 964
(passenger aircraft)	
Environmentally hazardous	: Yes
IMDG-Code	
UN number	: UN 3082.
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (Distillates (petroleum), hydrotreated middle, Phenol, isobu-tylenated, phosphate [Triphenyl phosphate > 25%])
<u>Class</u>	:9
Packing	: 111
Labels	: 9
EmS code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and var-iations in regional or country regulations.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation:Singapore Standard SS 586: Part 2 : 2014; Globally harmonised system of
classification and labelling of chemicals - Singapore's adaptations.
Singapore Standard SS 586: Part 3 : 2014; Preparation of safety data sheets
(SDS).
Guidelines on prevention and control of chemical hazard.

No information available.

Product name:	GulfSea Hydraulic SHVI 15	Page:	11/11
Supersedes date:	2020-11-07	Revision:	2020-11-07
Product No.:		SDS-ID:	HK-EN/2.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

Wording of H-statements:	
H304	May be fatal if swallowed and enters airways.
H227	Combustible liquid.
H315	Skin irritation

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature.