



PRODUCT DATA SHEET

GulfSea Gear Oil Series

Marine Gear Oil with EP additives specially formulated for all types of gears and bearings in extreme pressure conditions

Product Description

GulfSea Gear Oil series are high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions. These are blended from high quality base stocks and sulphur-phosphorous type extreme pressure additive system that gives excellent load carrying capability to provide protection against shock loading and wear. The high thermo-oxidative stability of the oil helps resist high temperature deposit formation and oil thickening. In addition, these oils also possess excellent water separation characteristics and offer resistance to foaming. These oils exceed the performance requirements of various industry specifications viz. DIN 51517 Part 3, ISO 12925-1 Type CKC/D, AGMA 9005 F16 Antiscuff, David Brown S1.53 101, US Steel 224, Ortinghaus Clutch and Siemens MD.

Features & Benefits

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/moisture.

Applications

- Wide range of industrial spur, helical, bevel and steel-on-steel worm gears.
- Heavy-duty industrial enclosed gears operating under heavy or shock loading conditions and requiring extreme pressure performance.
- Journal and roller contact industrial bearings operating at low speeds and high loads.
- Suitable for splash, mist and circulating systems.
- Marine gear applications.
- The shelf life of GulfSea Gear Oil can be extended when stored in an area away from sunlight and extreme heat.



PRODUCT DATA SHEET

Typical Properties

GulfSea Gear Oil Series								
	68	100	150	220	320	460	680	
ISO Viscosity grades	68	100	150	220	320	460	680	
Meets the following Specifications								
DIN 51517 Part 3	X	X	X	X	X	X	X	X
ISO 12925-1 Type CKC/CKD	X	X	X	X	X	X	X	X
AGMA 9005 F16 Antiscuff	X	X	X	X	X	X	X	X
David Brown S1.53 101 (M,A,E)	X	X	X	X	X	X	X	X
US Steel 224	X	X	X	X	X	X	X	X
Ortlinghaus Clutch		X	X	X				
Siemens MD for Flender Gearboxes		X	X	X	X	X	X	X
Typical Properties								
Test Parameters	ASTM Method	Test Values						
Viscosity @ 40 °C, cSt	D 445	68.4	101.0	149.0	216.3	315.7	461.3	682.4
Viscosity Index	D 2270	101	98	97	97	97	97	102
Flash Point, °C	D 92	224	240	246	246	253	262	255
Pour Point, °C	D 97	-27	-24	-21	-21	-18	-12	-12
Density @ 15°C, Kg/l	D 1298	0.884	0.885	0.890	0.893	0.901	0.904	0.904
FZG, fail load stage	DIN 51324	>12	>12	>12	>12	>12	>12	>12
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion	D 130	1b	1b	1b	1b	1b	1b	1b
Emulsion test 30 minute max	@ 54°C	Pass	-	-	-	-	-	-
	@ 82°C	-	Pass	Pass	Pass	Pass	Pass	Pass

Jan 2019