



Marine

PRODUCT DATA SHEET

GulfSea HT Oil 32

Marine Heat Transfer Mineral Oil specially formulated for Liquid Heat Circulation of Heat Transfer equipment with high resistance to oxidation

Product Description

GulfSea HT Oil 32 is premium quality heat transfer oil intended for use in closed indirect heating systems. It is formulated from highly refined base stocks to provide excellent oxidation stability and resistance against thermal cracking. It possesses high specific heat and thermal conductivity to provide more rapid heat dissipation and its ability to flow rapidly at low temperatures ensures quick circulation at start-up and reduced risk of local over-heating. Although GulfSea HT Oil 32 is thermally very stable and is capable of offering extended service life without viscosity increase or deposit formation, it should be realised that the working life depends to a considerable extent on the effectiveness of the measures taken to exclude air. GulfSea HT Oil 32 is primarily intended for use in enclosed and sealed heating systems where the maximum bulk oil temperature does not exceed 315 °C.

Features & Benefits

- Excellent thermal and oxidation stability minimises deposit formation and viscosity increase leading to extended service life and reduced downtime.
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315 °C with minimal interference with heat transfer capability.
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation.
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local over-heating.
- Non corrosive to aluminum, steel, copper, brass or bronze.
- Non-toxicity of this oil provides easy disposal of used oil.

Applications

- Closed, indirect heating and cooling systems equipped with expansion tanks in all kinds of industrial processes operating at bulk oil temperatures up to 315 °C.
- Open heating systems provided that the bulk oil temperature does not exceed 180 °C.

Typical Properties

GulfSea HT Oil 32		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 40 °C, cSt	D 445	32.2
Viscosity Index	D 2270	102
Flash Point, °C	D 92	230
Fire Point, °C	D 92	255
Pour Point, °C	D 97	-12
Density @ 15°C, Kg/l	D 1298	0.868

July 2014