



## GulfSea Synth LPG Compressor Oil

### Gulf Marine Pte. Ltd.

Chemwatch: 5624-43

Version No: 4.1

Safety Data Sheet in accordance with SS 586-3:2022

Issue Date: 28/06/2024

Print Date: 07/05/2025

S.GHS.SGP.EN.E

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

##### Product Identifier

|                               |                                  |
|-------------------------------|----------------------------------|
| Product name                  | GulfSea Synth LPG Compressor Oil |
| Chemical Name                 | Not Applicable                   |
| Synonyms                      | Not Available                    |
| Chemical formula              | Not Applicable                   |
| Other means of identification | 2SC515000-82                     |

##### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Compressor Oil<br>Use according to manufacturer's directions. |
|--------------------------|---|

##### Details of the manufacturer or importer of the safety data sheet

|                         |                               |
|-------------------------|-------------------------------|
| Registered company name | Gulf Marine Pte. Ltd.         |
| Address                 | 37 Tuas Road 638503 Singapore |
| Telephone               | +65 6592 0120                 |
| Fax                     | Not Available                 |
| Website                 | Not Available                 |
| Email                   | sds@gulf-marine.com           |

##### Emergency telephone number

|                                     |                       |
|-------------------------------------|-----------------------|
| Association / Organisation          | Gulf Marine Pte. Ltd. |
| Emergency telephone number(s)       | +65 6592 0120         |
| Other emergency telephone number(s) | Not Available         |

#### SECTION 2 Hazards identification

##### Classification of the substance or mixture

|                |   |
|----------------|---|
| Classification | Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Carcinogenicity Category 1A |
|----------------|---|

##### Label elements

|                     |        |
|---------------------|--------|
| Hazard pictogram(s) |        |
| Signal word         | Danger |

##### Hazard statement(s)

|      |                            |
|------|----------------------------|
| H315 | Causes skin irritation.    |
| H318 | Causes serious eye damage. |
| H350 | May cause cancer.          |

##### Precautionary statement(s) Prevention

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P264 | Wash all exposed external body areas thoroughly after handling.                  |

Precautionary statement(s) Response

|                |  |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/ attention.  |
| P310           | Immediately call a POISON CENTER/doctor/physician/first aider.   |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |

Precautionary statement(s) Storage

|      |                  |
|------|------------------|
| P405 | Store locked up. |
|------|------------------|

Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

Other hazards

Ingestion may produce health damage\*.  
Cumulative effects may result following exposure\*.  
Possible skin sensitizer\*.  
\*LIMITED EVIDENCE

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No        | % [weight] | Name                                       | Synonyms   | Chemical formula                                       |
|---------------|------------|--|--|--|
| 9038-95-3     | <60        | butyl alcohol propoxylated                 | C4 H10 O.(C3 H6 O.C2 H4 O)x; butyl ether propoxylated; 1-[2-[2-(3-methoxypropoxy)propoxy]ethoxy]butane (9:10); 2-(1-butoxypropan-2-yloxy)ethanol; PPG-10-buteth-9; oxirane, methyl-, polymer with oxirane, butyl ether; PPG-26-buteth-26; butyl polyoxyalkylene ethers; butyl PPG ethers; butyl PPG/ PEG ethers; Buteth-3 (polyethylene glycol ether of butyl alcohol) CAS RN: 143 -22-6 | C10H22O4[C13H28O4](C3H6O)nC4H10O[C4H10O.(C3H6O.C2H4O)x |
| Not Available | balance    | Ingredients determined not to be hazardous |  | Not Available  |

SECTION 4 First aid measures

Description of first aid measures

|              |  |
|--------------|--|
| Eye Contact  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"><li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li><li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li><li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li><li>▶ Transport to hospital or doctor without delay.</li><li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li></ul> |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"><li>▶ Immediately remove all contaminated clothing, including footwear.</li><li>▶ Flush skin and hair with running water (and soap if available).</li><li>▶ Seek medical attention in event of irritation.</li></ul>  |
| Inhalation   | <ul style="list-style-type: none"><li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li><li>▶ Other measures are usually unnecessary.</li></ul>   |
| Ingestion    | <ul style="list-style-type: none"><li>▶ If swallowed do <b>NOT</b> induce vomiting.</li><li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li><li>▶ Observe the patient carefully.</li><li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li><li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li><li>▶ Seek medical advice.</li></ul>  |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

|                      |  |
|----------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|----------------------|--|

Advice for firefighters

|                       |   |
|-----------------------|---|
| Fire Fighting         | <ul style="list-style-type: none"><li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li><li>▶ Wear full body protective clothing with breathing apparatus.</li><li>▶ Prevent, by any means available, spillage from entering drains or water course.</li><li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li><li>▶ Avoid spraying water onto liquid pools.</li><li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li><li>▶ Cool fire exposed containers with water spray from a protected location.</li><li>▶ If safe to do so, remove containers from path of fire.</li></ul> |
| Fire/Explosion Hazard | <ul style="list-style-type: none"><li>▶ Combustible.</li><li>▶ Slight fire hazard when exposed to heat or flame.</li><li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li><li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li><li>▶ May emit acrid smoke.</li><li>▶ Mists containing combustible materials may be explosive.</li></ul> Combustion products include:<br>carbon dioxide (CO2)<br>other pyrolysis products typical of burning organic material.<br>May emit poisonous fumes.<br>May emit corrosive fumes.   |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

|              |  |
|--------------|--|
| Minor Spills | <p>Slippery when spilt.</p> <ul style="list-style-type: none"><li>▶ Remove all ignition sources.</li><li>▶ Clean up all spills immediately.</li><li>▶ Avoid breathing vapours and contact with skin and eyes.</li><li>▶ Control personal contact with the substance, by using protective equipment.</li><li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li><li>▶ Wipe up.</li><li>▶ Place in a suitable, labelled container for waste disposal.</li></ul>   |
| Major Spills | <p>Slippery when spilt.<br/>Moderate hazard.</p> <ul style="list-style-type: none"><li>▶ Clear area of personnel and move upwind.</li><li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li><li>▶ Wear breathing apparatus plus protective gloves.</li><li>▶ Prevent, by any means available, spillage from entering drains or water course.</li><li>▶ No smoking, naked lights or ignition sources.</li><li>▶ Increase ventilation.</li><li>▶ Stop leak if safe to do so.</li><li>▶ Contain spill with sand, earth or vermiculite.</li><li>▶ Collect recoverable product into labelled containers for recycling.</li><li>▶ Absorb remaining product with sand, earth or vermiculite.</li><li>▶ Collect solid residues and seal in labelled drums for disposal.</li><li>▶ Wash area and prevent runoff into drains.</li><li>▶ If contamination of drains or waterways occurs, advise emergency services.</li></ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

|               |  |
|---------------|--|
| Safe handling | <ul style="list-style-type: none"><li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li><li>▶ Overheating of ethoxylates/ alkoxyates in air should be avoided. When some ethoxylates are heated vigorously in the presence of air or oxygen, at temperatures exceeding 160 C, they may undergo exothermic oxidative degeneration resulting in self-heating and autoignition.</li><li>▶ Nitrogen blanketing will minimise the potential for ethoxylate oxidation. Prolonged storage in the presence of air or oxygen may cause product degradation. Oxidation is not expected when stored under a nitrogen atmosphere. Inert gas blanket and breathing system needed to maintain color stability. Use dry inert gas having at least -40 C dew point.</li><li>▶ Trace quantities of ethylene oxide may be present in the material. Although these may accumulate in the headspace of storage and transport vessels, concentrations are not expected to exceed levels which might produce a flammability or worker exposure hazard.</li><li>▶ Avoid all personal contact, including inhalation.</li><li>▶ Wear protective clothing when risk of exposure occurs.</li><li>▶ Use in a well-ventilated area.</li><li>▶ Prevent concentration in hollows and sumps.</li><li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li><li>▶ Avoid smoking, naked lights or ignition sources.</li><li>▶ Avoid contact with incompatible materials.</li><li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li><li>▶ Keep containers securely sealed when not in use.</li></ul> |
|---------------|--|

|                   |   |
|-------------------|---|
|                   | <ul style="list-style-type: none"><li>▶ Avoid physical damage to containers.</li><li>▶ Always wash hands with soap and water after handling.</li><li>▶ Work clothes should be laundered separately.</li><li>▶ Use good occupational work practice.</li><li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li><li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li></ul>  |
| Other information | <p>Ethoxylates/ alkoxyates react slowly with air or oxygen and may generate potentially sensitising intermediates (haptens).. Storage under heated conditions in the presence of air or oxygen increases reaction rate. For example, after storing at 95 F/ 35 C for 30 days in the presence of air, there is measurable oxidation of the ethoxylate. Lower temperatures will allow for longer storage time and higher temperatures will shorten the storage time if stored under an air or oxygen atmosphere.</p> <ul style="list-style-type: none"><li>▶ Store in original containers.</li><li>▶ Keep containers securely sealed.</li><li>▶ No smoking, naked lights or ignition sources.</li><li>▶ Store in a cool, dry, well-ventilated area.</li><li>▶ Store away from incompatible materials and foodstuff containers.</li><li>▶ Protect containers against physical damage and check regularly for leaks.</li><li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li></ul> |

Conditions for safe storage, including any incompatibilities

|                         |   |
|-------------------------|---|
| Suitable container      | <p>For ethoxylates suitable containers include carbon steel coated with baked phenolic. Any moisture may cause rusting of carbon steel.</p> <p>If product is moisture free, uncoated carbon steel tanks may be used.</p> <ul style="list-style-type: none"><li>▶ Metal can or drum</li><li>▶ Packaging as recommended by manufacturer.</li><li>▶ Check all containers are clearly labelled and free from leaks.</li></ul> |
| Storage incompatibility | <ul style="list-style-type: none"><li>▶ Avoid reaction with oxidising agents</li></ul>  |

SECTION 8 Exposure controls / personal protection

Control parameters







Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

| Ingredient                 | Original IDLH | Revised IDLH  |
|----------------------------|---------------|---------------|
| butyl alcohol propoxylated | Not Available | Not Available |

Exposure controls

| Appropriate engineering controls  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table><tr><th>Type of Contaminant:</th><th>Air Speed:</th></tr><tr><td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td><td>0.25-0.5 m/s (50-100 f/min)</td></tr><tr><td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s (100-200 f/min.)</td></tr><tr><td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min)</td></tr><tr><td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td><td>2.5-10 m/s (500-2000 f/min.)</td></tr></table> <p>Within each range the appropriate value depends on:</p> <table><tr><th>Lower end of the range</th><th>Upper end of the range</th></tr><tr><td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr><tr><td>2: Contaminants of low toxicity or of nuisance value only</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood - local control only</td></tr></table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air) | 0.25-0.5 m/s (50-100 f/min) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood - local control only |
|---|---|----------------------|------------|---|-----------------------------|---|----------------------------|--|---------------------------|--|------------------------------|------------------------|------------------------|---|---------------------------------|---|----------------------------------|----------------------------------|-------------------------------|---|------------------------------------|
| Type of Contaminant:  | Air Speed:  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| solvent, vapours, degreasing etc., evaporating from tank (in still air)   | 0.25-0.5 m/s (50-100 f/min)   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min)   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s (500-2000 f/min.)  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| Lower end of the range  | Upper end of the range  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 2: Contaminants of low toxicity or of nuisance value only   | 2: Contaminants of high toxicity  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 4: Large hood or large air mass in motion   | 4: Small hood - local control only  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| Individual protection measures, such as personal protective equipment   | <div></div>   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |

## GulfSea Synth LPG Compressor Oil

|                                |   |
|--------------------------------|---|
| <b>Eye and face protection</b> | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>  |
| <b>Skin protection</b>         | See Hand protection below   |
| <b>Hands/feet protection</b>   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>         | See Other protection below  |
| <b>Other protection</b>        | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>  |

**Respiratory protection**

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10                           | 1000   | A-AUS / Class1       | -                    |
| up to 50                           | 1000   | -                    | A-AUS / Class 1      |
| up to 50                           | 5000   | Airline *            | -                    |
| up to 100                          | 5000   | -                    | A-2                  |
| up to 100                          | 10000  | -                    | A-3                  |
| 100+                               |  |                      | Airline**            |

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

**SECTION 9 Physical and chemical properties**

Continued...

## GulfSea Synth LPG Compressor Oil

## Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                     | Clear to slight yellow colored liquid with petroleum like odor; mixes with water. |  |                |
| <b>Physical state</b>                                 | Liquid  | <b>Relative density (Water = 1)</b>                        | 1.035-1.055    |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b>             | Not Available  |
| <b>Odour threshold</b>                                | Not Available   | <b>Auto-ignition temperature (°C)</b>                      | Not Available  |
| <b>pH (as supplied)</b>                               | Not Available   | <b>Decomposition temperature (°C)</b>                      | Not Available  |
| <b>Melting point / freezing point (°C)</b>            | Not Available   | <b>Viscosity (cSt)</b>                                     | 20.6-320       |
| <b>Initial boiling point and boiling range (°C)</b>   | >392  | <b>Molecular weight (g/mol)</b>                            | Not Applicable |
| <b>Flash point (°C)</b>                               | = 236 (ASTM D-92)   | <b>Taste</b>   | Not Available  |
| <b>Evaporation rate</b>                               | Not Available   | <b>Explosive properties</b>                                | Not Available  |
| <b>Flammability</b>                                   | Not Applicable  | <b>Oxidising properties</b>                                | Not Available  |
| <b>Upper Explosive Limit (%)</b>                      | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>                    | Not Available  |
| <b>Lower Explosive Limit (%)</b>                      | Not Available   | <b>Volatile Component (%vol)</b>                           | Not Available  |
| <b>Vapour pressure (kPa)</b>                          | <0.1 mmHg   | <b>Gas group</b>   | Not Available  |
| <b>Solubility in water</b>                            | Miscible  | <b>pH as a solution (1%)</b>                               | Not Available  |
| <b>Vapour density (Air = 1)</b>                       | >1  | <b>VOC g/L</b>   | Not Available  |
| <b>Heat of Combustion (kJ/g)</b>                      | Not Available   | <b>Ignition Distance (cm)</b>                              | Not Available  |
| <b>Flame Height (cm)</b>                              | Not Available   | <b>Flame Duration (s)</b>                                  | Not Available  |
| <b>Enclosed Space Ignition Time Equivalent (s/m3)</b> | Not Available   | <b>Enclosed Space Ignition Deflagration Density (g/m3)</b> | Not Available  |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

## Information on toxicological effects

|   |   |
|---|---|
| <b>a) Acute Toxicity</b>                    | Based on available data, the classification criteria are not met.                       |
| <b>b) Skin Irritation/Corrosion</b>         | There is sufficient evidence to classify this material as skin corrosive or irritating. |
| <b>c) Serious Eye Damage/Irritation</b>     | There is sufficient evidence to classify this material as eye damaging or irritating    |
| <b>d) Respiratory or Skin sensitisation</b> | Based on available data, the classification criteria are not met.                       |
| <b>e) Mutagenicity</b>                      | Based on available data, the classification criteria are not met.                       |
| <b>f) Carcinogenicity</b>                   | There is sufficient evidence to classify this material as carcinogenic                  |
| <b>g) Reproductivity</b>                    | Based on available data, the classification criteria are not met.                       |
| <b>h) STOT - Single Exposure</b>            | Based on available data, the classification criteria are not met.                       |
| <b>i) STOT - Repeated Exposure</b>          | Based on available data, the classification criteria are not met.                       |
| <b>j) Aspiration Hazard</b>                 | Based on available data, the classification criteria are not met.                       |

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.<br>Inhalation hazard is increased at higher temperatures.   |
| <b>Ingestion</b>    | Accidental ingestion of the material may be damaging to the health of the individual.<br>Nonionic surfactants may produce localised irritation of the oral or gastrointestinal lining and induce vomiting and mild diarrhoea.   |
| <b>Skin Contact</b> | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.<br>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.<br>Non-ionic surfactants cause less irritation than other surfactants as they have less ability to denature protein in the skin.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| <b>Eye</b>          | If applied to the eyes, this material causes severe eye damage.   |

Continued...

|         |  |
|---------|--|
|         | Non-ionic surfactants can cause numbing of the cornea, which masks discomfort normally caused by other agents and leads to corneal injury. Irritation varies depending on the duration of contact, the nature and concentration of the surfactant.     |
| Chronic | Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.<br>Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation. |

|                                  |  |  |
|----------------------------------|--|--|
| GulfSea Synth LPG Compressor Oil | TOXICITY   | IRRITATION   |
|                                  | Not Available                                      | Not Available  |
| butyl alcohol propoxylated       | TOXICITY   | IRRITATION   |
|                                  | Dermal (rabbit) LD50: 13340 mg/kg <sup>[2]</sup>   | Eye (Rodent - rabbit): 20mg/24H - Moderate                       |
|                                  | Inhalation (Rat) LC50: 0.147 mg/L4h <sup>[2]</sup> | Eye (Rodent - rabbit): 500mg                                     |
|                                  | Oral (Rabbit) LD50; 1770 mg/kg <sup>[2]</sup>      | Eye (Rodent - rabbit): 500mg                                     |
|                                  |  | Eye (Rodent - rabbit): 500mg/24H - Mild                          |
|                                  |  | Eye (Rodent - rabbit): 500mg/24H - Mild                          |
|                                  |  | Eye (Rodent - rabbit): 50mg - Severe                             |
|                                  |  | Eye (Rodent - rabbit): 50mg - Severe                             |
|                                  |  | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|                                  |  | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|                                  |  | Skin (Rodent - rabbit): 10mg/24H - Mild                          |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg - Mild                             |
|                                  |  | Skin (Rodent - rabbit): 500mg/24H - Mild                         |
|                                  |  | Skin (Rodent - rabbit): 500mg/24H - Mild                         |
|                                  |  | Skin (Rodent - rabbit): 500mg/24H - Mild                         |
|                                  |  | Skin (Rodent - rabbit): 80mg/4H                                  |
|                                  |  | Skin (Rodent - rabbit): 80mg/4H - Mild                           |
|                                  |  | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|                                  |  | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |

|         |   |
|---------|---|
| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |
|---------|---|

|                            |  |
|----------------------------|--|
| BUTYL ALCOHOL PROPOXYLATED | <p>In general, the toxicity of the PPGs Butyl Ether decreased with increasing molecular weight; for example, PPG-40 Butyl Ether was less toxic than PPG-2 Butyl Ether. Mutagenicity data were not found on the PPGs Butyl Ether. However, an ether of molecular weight 800 Da (~PPG-13 Butyl Ether) was non-carcinogenic when fed to rats for 2 years. Because the PPGs Butyl Ethers undergo metabolic degradation; i.e., the butyl group are removed and oxidized, the PPG chains are split into random length fragments, the genotoxicity of the component chemicals, propylene glycol (PG) and n- Butyl Alcohol, were also considered. Both PG and n-Butyl Alcohol were non-mutagenic in mammalian and microbial assays. PG was non-carcinogenic in a 2-year feeding study using rats and in a lifetime dermal study using mice. These studies effectively eliminated the need for genotoxicity data on the PPG Butyl Ethers. There was concern about the irritancy potential of PPG-2 Butyl Ether. In animal irritation studies, the ingredient caused minor, transient erythema and desquamation; in addition, erythema, edema, ecchymosis, necrosis, and other changes were observed during an acute percutaneous study. PPG-2 Butyl Ether also caused minor to moderate conjunctival irritation and minor corneal injury. It was concluded that the PPG Butyl Ethers were safe for use in cosmetics when formulated to avoid irritation. The dermal LD50 of PPG-3 Butyl Ether was 2 g/kg in rats and rabbits, and the dermal LD50 of Buteth-3 in rats was 3.5 g/kg. The oral LD50 of PPG-3 Butyl Ether and of Buteth-3 in rats was 2 g/kg and 6.6 g/kg, respectively. Polypropyleneglycol butyl ethers (not defined) had a dermal and an oral LD50 of 2 g/kg and 0.3-2 g/kg bw, respectively,in mice.Buteth-3 (1000 mg/kg/day) was not toxic to rabbits in a 21-day dermal study; erythema, desquamation, and fissuring were observed In short-term oral toxicity studies in rats, PPG-3 Butyl Ether had a NOAEL of 1000 mg/kg bw; polypropylene glycol butyl ethers had a NOEL of 100 mg/kg bw/day for clinical observations, higher absolute and relative liver weights, and an increased incidence of liver and thyroid gland hypertrophy; and 1-(2-butoxy-1-methylethoxy)propan-2-ol had a NOAEL of 100 mg/kg/day based on very slight hepatocellular hypertrophy with no corresponding increases in liver weights in low-dose males. In a 90-day oral toxicity study, administration of up to 1000 mg/kg bw/day PPG-3 Butyl Ether to rats in drinking water produced treatment-related increases in absolute and relative liver and kidney weights. The NOAELs in rats and mice exposed to=3000 ppm methoxyisopropanol via inhalation for 2 yrs were 1000 ppm (based on slight body wt decreases in males and females) and 300 ppm (based on altered hepatocellular foci in males), respectively.Dermal application of propylene glycol butyl ether was not embryotoxic or teratogenic to rabbits (=100 mg/kg bw/day applied on days 7-18 of gestation) or rats (=1.0 ml/kg bw/day applied on days 6-16 of gestation). 1-(2-Butoxy-1-methyl-ethoxy)propan-2-ol (applied on days 6-16 or 6-15 of gestation) also was not embryotoxic or teratogenic in rats. No test-article related adverse developmental or reproductive effects were observed in rats dosed by gavage with up to 1000 mg/kg Buteth-3 or 1-(2-butoxy-1-methylethoxy)propan-2-ol or up to 500 mg/kg bw/day polypropylene glycol butyl ethers. In inhalation studies, exposure of rats to =1.0 mg/l air PPG-3 Methyl Ether did not have any teratogenic or reproductive effects. Exposure to 1000 and 3000 ppm methoxyisopropanol produced some adverse effects in a two-generation study in rats; adverse effects were not observed with 300 ppm. PPG-3 Butyl Ether was not genotoxic in vitro in the Ames test or in vivo in a mouse micronucleus assay. Propylene glycol butyl ether was not genotoxic in an Ames test or a mammalian chromosomal aberration assay in rat lymphocytes, andneither propylene glycol butyl ether or 1-(2-butoxy-1-methylethoxy)propan-2-ol were genotoxic in a mammalian cellmutation assay in CHO cell. In inhalation</p> |
|----------------------------|--|

carcinogenicity studies, mice and rats were exposed by whole body exposure to =3000 ppm methoxyisopropan-ol for 2 yrs. An increase in S-phase DNA synthesis and in MFO activity in the liver was observed in high-dose male mice and rats. Renal epithelial tumors were not observed, and the NOEL for carcinogenicity was 3000 ppm for mice and rats. Undiluted PPG-3 Butyl Ether was not irritating to rabbit skin or eyes, and it was not an irritant or sensitizer in guinea pigs. Polypropylene glycol butyl ethers were classified as non-corrosive in an EpiDermTM study

Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products.

Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation.

Humans have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents and other cleaning products. Exposure to these chemicals can occur through swallowing, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that relatively high volumes would have to occur to produce any toxic response. No death due to poisoning with alcohol ethoxylates has ever been reported. Studies show that alcohol ethoxylates have low toxicity through swallowing and skin contact.

Animal studies show these chemicals may produce gastrointestinal irritation, stomach ulcers, hair standing up, diarrhea and lethargy. Slight to severe irritation occurred when undiluted alcohol ethoxylates were applied to the skin and eyes of animals. These chemicals show no indication of genetic toxicity or potential to cause mutations and cancers. Toxicity is thought to be substantially lower than that of nonylphenol ethoxylates.

Some of the oxidation products of this group of substances may have sensitizing properties.

As they cause less irritation, nonionic surfactants are often preferred to ionic surfactants in topical products. However, their tendency to auto-oxidise also increases their irritation. Due to their irritating effect it is difficult to diagnose allergic contact dermatitis (ACD) by patch testing. Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No adverse reproductive or developmental effects were observed.

Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma. Death may result in experimental animal. However, repeated exposure may cause dose dependent damage to the kidneys as well as reproductive and developmental defects.

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✓ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✗ |

Legend: ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

Other information  
Not Available

SECTION 12 Ecological information

|                                  |               |                    |  |               |               |
|----------------------------------|---------------|--------------------|--|---------------|---------------|
| Toxicity                         |               |                    |  |               |               |
| GulfSea Synth LPG Compressor Oil | Endpoint      | Test Duration (hr) | Species  | Value         | Source        |
|                                  | Not Available | Not Available      | Not Available  | Not Available | Not Available |
| butyl alcohol propoxylated       | Endpoint      | Test Duration (hr) | Species  | Value         | Source        |
|                                  | EC50          | 48h                | Crustacea  | >500mg/l      | 1             |
|                                  | EC50          | 72h                | Algae or other aquatic plants  | >500mg/l      | 1             |
|                                  | EC50          | 96h                | Algae or other aquatic plants  | 744.74mg/l    | 2             |
|                                  | NOEC(ECx)     | 72h                | Algae or other aquatic plants  | 62.5mg/l      | 2             |
|                                  | LC50          | 96h                | Fish   | 1350mg/l      | 1             |
|                                  | LC50          | 96h                | Fish   | 564mg/l       | 2             |
|                                  | EC50          | 48h                | Crustacea  | >100mg/l      | 2             |
|                                  | EC50          | 72h                | Algae or other aquatic plants  | 445mg/l       | 2             |
|                                  | NOEC(ECx)     | 96h                | Algae or other aquatic plants  | <15.9mg/l     | 2             |
|                                  | EC50          | 96h                | Algae or other aquatic plants  | 315mg/l       | 2             |
|                                  | EC50          | 48h                | Crustacea  | 89-101mg/L    | 4             |
|                                  | EC50(ECx)     | 48h                | Crustacea  | 89-101mg/L    | 4             |
|                                  | LC50          | 96h                | Fish   | 48-52mg/L     | 4             |
|                                  | Legend:       |                    | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |               |               |

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
**DO NOT** discharge into sewer or waterways.

| Persistence and degradability |                         |                  |
|-------------------------------|-------------------------|------------------|
| Ingredient                    | Persistence: Water/Soil | Persistence: Air |
| butyl alcohol propoxylated    | LOW                     | LOW              |

|                            |                       |
|----------------------------|-----------------------|
| Bioaccumulative potential  |                       |
| Ingredient                 | Bioaccumulation       |
| butyl alcohol propoxylated | LOW (LogKOW = 1.2706) |



Mobility in soil

| Ingredient                 | Mobility           |
|----------------------------|--------------------|
| butyl alcohol propoxylated | LOW (Log KOC = 10) |

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

|                              |   |
|------------------------------|---|
| Product / Packaging disposal | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.<br>A Hierarchy of Controls seems to be common - the user should investigate: <ul style="list-style-type: none"><li>Reduction</li><li>Reuse</li><li>Recycling</li><li>Disposal (if all else fails)</li></ul> This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. <ul style="list-style-type: none"><li><b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li><li>It may be necessary to collect all wash water for treatment before disposal.</li><li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li><li>Where in doubt contact the responsible authority.</li><li>Recycle wherever possible or consult manufacturer for recycling options.</li><li>Consult State Land Waste Authority for disposal.</li><li>Bury or incinerate residue at an approved site.</li><li>Recycle containers if possible, or dispose of in an authorised landfill.</li></ul> |
|                              |   |

SECTION 14 Transport information

Labels Required

|                  |    |
|------------------|----|
| Marine Pollutant | NO |
|------------------|----|

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name               | Group         |
|----------------------------|---------------|
| butyl alcohol propoxylated | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name               | Ship Type     |
|----------------------------|---------------|
| butyl alcohol propoxylated | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

butyl alcohol propoxylated is found on the following regulatory lists

Not Applicable

Additional Regulatory Information

Not Applicable

National Inventory Status

| National Inventory                              | Status                          |
|---|---------------------------------|
| Australia - AIIC / Australia Non-Industrial Use | Yes                             |
| Canada - DSL                                    | Yes                             |
| Canada - NDSL                                   | No (butyl alcohol propoxylated) |
| China - IECSC                                   | Yes                             |
| Europe - EINEC / ELINCS / NLP                   | Yes                             |
| Japan - ENCS                                    | Yes                             |

| National Inventory  | Status  |
|---------------------|---|
| Korea - KECI        | Yes   |
| New Zealand - NZIoC | Yes   |
| Philippines - PICCS | Yes   |
| USA - TSCA          | All chemical substances in this product have been designated as TSCA Inventory 'Active'   |
| Taiwan - TCSI       | Yes   |
| Mexico - INSQ       | Yes   |
| Vietnam - NCI       | Yes   |
| Russia - FBEPH      | Yes   |
| Legend:             | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 28/06/2024 |
| Initial Date  | 07/08/2023 |

Other information

Ingredients with multiple cas numbers

| Name                       | CAS No  |
|----------------------------|---|
| butyl alcohol propoxylated | 9065-63-8, 1033553-65-9, 9038-95-3, 9003-13-8, 55934-93-5, 143-22-6 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.