



## GulfSea BD Hydraulic Oil 32, 46, 68, 100

### Gulf Marine Pte. Ltd.

Chemwatch: 5624-73

Version No: 3.1

Safety Data Sheet in accordance with SS 586-3:2022

Initial Date: 14/08/2023

Revision Date: 27/09/2023

Print Date: 06/03/2026

S.GHS.SGP.EN.E

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | GulfSea BD Hydraulic Oil 32, 46, 68, 100           |
| Chemical Name                 | Not Applicable                                     |
| Synonyms                      | Not Available                                      |
| Chemical formula              | Not Applicable                                     |
| Other means of identification | 2BH55100-67, 2BH55320-67, 2BH55460-67, 2BH55680-67 |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | Hydraulic oil<br>Use according to manufacturer's directions. |
|--------------------------|--|

### Details of the manufacturer or importer of the safety data sheet

|                         |                               |
|-------------------------|-------------------------------|
| Registered company name | Gulf Marine Pte. Ltd.         |
| Address                 | 37 Tuas Road 638503 Singapore |
| Telephone               | +65 6592 0120                 |
| Fax                     | Not Available                 |
| Website                 | Not Available                 |
| Email                   | sds@gulf-marine.com           |

### Emergency telephone number

|                                     |                       |
|-------------------------------------|-----------------------|
| Association / Organisation          | Gulf Marine Pte. Ltd. |
| Emergency telephone number(s)       | +65 6592 0120         |
| Other emergency telephone number(s) | Not Available         |

## SECTION 2 Hazards identification

### Classification of the substance or mixture

|                |                              |
|----------------|------------------------------|
| Classification | Aspiration Hazard Category 1 |
|----------------|------------------------------|

### Label elements

|                     |        |
|---------------------|--------|
| Hazard pictogram(s) |        |
| Signal word         | Danger |

### Hazard statement(s)

|      |   |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |
|------|---|

### Precautionary statement(s) Prevention

Not Applicable

**Precautionary statement(s) Response**

|                  |  |
|------------------|--|
| <b>P301+P310</b> | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. |
| <b>P331</b>      | Do NOT induce vomiting.  |

**Precautionary statement(s) Storage**

|             |                  |
|-------------|------------------|
| <b>P405</b> | Store locked up. |
|-------------|------------------|

**Precautionary statement(s) Disposal**

|             |  |
|-------------|--|
| <b>P501</b> | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

**Other hazards**

Not Applicable

No further product hazard information.

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No        | %[weight] | Name   | Synonyms   | Chemical formula |
|---------------|-----------|--|--|------------------|
| 1000172-11-1  | 20-50     | <u>7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated</u> | C28-80H58-162; 7-methylpentadecane, tetra-1-decene, dimer, trimer, hydrogenated; pentadecane, 7-methylene, mixed with 1-tetradecene, dimers and trimers, hydrogenated; hydrogenated tetradecenyl/methylpentadecene | C28-80H58-162    |
| Not Available | NotSpec   | proprietary ingredients  |  | Not Available    |

**SECTION 4 First aid measures****Description of first aid measures**

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>   |
| <b>Skin Contact</b> | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>  |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul> |

**Indication of any immediate medical attention and special treatment needed**

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

**SECTION 5 Firefighting measures****Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**Special hazards arising from the substrate or mixture**

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

**Advice for firefighters**

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> </ul>  |

Continued...

- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
  - ▶ May emit acrid smoke.
  - ▶ Mists containing combustible materials may be explosive.
- Combustion products include:
- ▶ carbon dioxide (CO<sub>2</sub>)
  - ▶ other pyrolysis products typical of burning organic material.
- May emit poisonous fumes.

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>  |
| <b>Major Spills</b> | <p>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                          |   |
|--------------------------|---|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid skin contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT</b> allow material to come in direct contact with human skin or eyes.</li> <li>▶ <b>DO NOT</b> allow material to come in contact with exposed food or food contact surfaces.</li> <li>▶ Suitable PPE must be worn at all times.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>  |

### Conditions for safe storage, including any incompatibilities

|                                |  |
|--------------------------------|--|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>   |

## SECTION 8 Exposure controls / personal protection

### Control parameters


Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

### Exposure controls

Continued...

| <p><b>Appropriate engineering controls</b></p>  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" data-bbox="384 472 1493 712"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" data-bbox="384 770 1150 927"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood - local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air) | 0.25-0.5 m/s (50-100 f/min) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood - local control only |
|---|---|----------------------|------------|---|-----------------------------|---|----------------------------|--|---------------------------|--|------------------------------|------------------------|------------------------|---|---------------------------------|---|----------------------------------|----------------------------------|-------------------------------|---|------------------------------------|
| Type of Contaminant:  | Air Speed:  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| solvent, vapours, degreasing etc., evaporating from tank (in still air)   | 0.25-0.5 m/s (50-100 f/min)   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min)   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s (500-2000 f/min.)  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| Lower end of the range  | Upper end of the range  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 2: Contaminants of low toxicity or of nuisance value only   | 2: Contaminants of high toxicity  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| 4: Large hood or large air mass in motion   | 4: Small hood - local control only  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| <p><b>Individual protection measures, such as personal protective equipment</b></p>   |    |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| <p><b>Eye and face protection</b></p>   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>   |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| <p><b>Skin protection</b></p>   | <p>See Hand protection below</p>  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |
| <p><b>Hands/feet protection</b></p>   | <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>- frequency and duration of contact,</li> <li>- chemical resistance of glove material,</li> <li>- glove thickness and</li> <li>- dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> </ul> <ul style="list-style-type: none"> <li>- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>- Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>- Excellent when breakthrough time &gt; 480 min</li> <li>- Good when breakthrough time &gt; 20 min</li> <li>- Fair when breakthrough time &lt; 20 min</li> <li>- Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p>  |                      |            |   |                             |   |                            |  |                           |  |                              |                        |                        |   |                                 |   |                                  |                                  |                               |   |                                    |

|                         |   |
|-------------------------|---|
|                         | <ul style="list-style-type: none"> <li>Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <ul style="list-style-type: none"> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> |
| <b>Body protection</b>  | See Other protection below  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>  |

### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10                           | 1000   | A-AUS / Class1       | -                    |
| up to 50                           | 1000   | -                    | A-AUS / Class 1      |
| up to 50                           | 5000   | Airline *            | -                    |
| up to 100                          | 5000   | -                    | A-2                  |
| up to 100                          | 10000  | -                    | A-3                  |
| 100+                               |  |                      | Airline**            |

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

|  |  |   |                |
|--|--|---|----------------|
| <b>Appearance</b>  | Light yellow liquid with characteristic odor; does not mix with water. |   |                |
| <b>Physical state</b>  | Liquid   | <b>Relative density (Water = 1)</b>                                   | 0.91-0.92      |
| <b>Odour</b>   | Not Available  | <b>Partition coefficient n-octanol / water</b>                        | Not Available  |
| <b>Odour threshold</b>   | Not Available  | <b>Auto-ignition temperature (°C)</b>                                 | Not Available  |
| <b>pH (as supplied)</b>  | Not Applicable   | <b>Decomposition temperature (°C)</b>                                 | Not Available  |
| <b>Melting point / freezing point (°C)</b>                       | Not Available  | <b>Viscosity (cSt)</b>  | 32-100         |
| <b>Initial boiling point and boiling range (°C)</b>              | Not Available  | <b>Molecular weight (g/mol)</b>                                       | Not Applicable |
| <b>Flash point (°C)</b>  | >180   | <b>Taste</b>  | Not Available  |
| <b>Evaporation rate</b>  | Not Available  | <b>Explosive properties</b>   | Not Available  |
| <b>Flammability</b>  | Not Applicable   | <b>Oxidising properties</b>   | Not Available  |
| <b>Upper Explosive Limit (%)</b>                                 | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b>                               | Not Available  |
| <b>Lower Explosive Limit (%)</b>                                 | Not Available  | <b>Volatile Component (%vol)</b>                                      | Not Available  |
| <b>Vapour pressure (kPa)</b>                                     | Not Available  | <b>Gas group</b>  | Not Available  |
| <b>Solubility in water</b>                                       | Immiscible   | <b>pH as a solution (1%)</b>  | Not Applicable |
| <b>Vapour density (Air = 1)</b>                                  | Not Available  | <b>VOC g/L</b>  | Not Available  |
| <b>Heat of Combustion (kJ/g)</b>                                 | Not Available  | <b>Ignition Distance (cm)</b>   | Not Available  |
| <b>Flame Height (cm)</b>   | Not Available  | <b>Flame Duration (s)</b>   | Not Available  |
| <b>Enclosed Space Ignition Time Equivalent (s/m<sup>3</sup>)</b> | Not Available  | <b>Enclosed Space Ignition Deflagration Density (g/m<sup>3</sup>)</b> | Not Available  |

## SECTION 10 Stability and reactivity

|                           |  |
|---------------------------|--|
| <b>Reactivity</b>         | See section 7  |
| <b>Chemical stability</b> | <ul style="list-style-type: none"> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul> |

|                                    |               |
|------------------------------------|---------------|
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid                | See section 7 |
| Incompatible materials             | See section 7 |
| Hazardous decomposition products   | See section 5 |

## SECTION 11 Toxicological information

### Information on toxicological effects

|                                      |  |
|--------------------------------------|--|
| a) Acute Toxicity                    | Based on available data, the classification criteria are not met.              |
| b) Skin Irritation/Corrosion         | Based on available data, the classification criteria are not met.              |
| c) Serious Eye Damage/Irritation     | Based on available data, the classification criteria are not met.              |
| d) Respiratory or Skin sensitisation | Based on available data, the classification criteria are not met.              |
| e) Mutagenicity                      | Based on available data, the classification criteria are not met.              |
| f) Carcinogenicity                   | Based on available data, the classification criteria are not met.              |
| g) Reproductivity                    | Based on available data, the classification criteria are not met.              |
| h) STOT - Single Exposure            | Based on available data, the classification criteria are not met.              |
| i) STOT - Repeated Exposure          | Based on available data, the classification criteria are not met.              |
| j) Aspiration Hazard                 | There is sufficient evidence to classify this material as an aspiration hazard |

|              |   |
|--------------|---|
| Inhaled      | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.   |
| Ingestion    | Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)<br>The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.  |
| Skin Contact | The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye          | Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).  |
| Chronic      | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.  |

|   |   |                   |
|---|---|-------------------|
| GulfSea BD Hydraulic Oil 32, 46, 68, 100                            | <b>TOXICITY</b>                               | <b>IRRITATION</b> |
|   | Not Available                                 | Not Available     |
| 7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated | <b>TOXICITY</b>                               | <b>IRRITATION</b> |
|   | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> | Not Available     |
|   | Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>   |                   |



**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |  |  |  |
|---|--|--|--|
| 7-METHYLENAPENTADECENE, 1-TETRADECENE DIMERS, TRIMERS, HYDROGENATED | For poly-alpha-olefins (PAOs):<br>PAOs are highly branched, isoparaffinic chemicals produced by oligomerisation of 1-octene, 1-decene and/or 1-dodecene. The crude polyalphaolefin mixture is then distilled into appropriate product fractions to meet specific viscosity specifications and hydrogenated. In existing data, there appears to be no data to show that these structural analogs cause health effects. In addition, there is evidence in the literature that alkanes with 30 or more carbon atoms are unlikely to be absorbed when given by mouth. The physical and chemical properties make it unlikely that significant absorption into the body will occur. There are also no functional groups on PAO molecules that are biologically active. PAOs also have low volatility, so that exposure is unlikely to occur by inhalation. The high viscosity of these substances also makes it hard to generate a high concentration of breathable particles in air.<br>Acute toxicity: Animal testing shows that PAOs have relatively low acute toxicity.<br>Repeat dose toxicity: Animal testing shows that PAOs show low repeat dose toxicity – some increased scaling of the skin occurred, with skin inflammation, after exposure at high doses.<br>Reproductive toxicity: Animal testing suggested that application of PAO to skin did not impair reproductive performance.<br>Genetic toxicity: Testing has not shown any evidence that PAOs cause mutations or chromosomal aberrations.<br>Cancer-causing potentials: Animal testing has not shown any propensity to cause tumours. While alpha-olefin polymers have similar properties to mineral oils, they do not contain polycyclic aromatic hydrocarbons, or other known cancer-causing materials.<br>No significant acute toxicological data identified in literature search. |  |  |
|   |  |  |  |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion         | ✗ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✗ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✓ |

Legend: ✗ Data either not available or does not fill the criteria for classification

Continued...

**Legend:**  – Data either not available or does not fit the criteria for classification  
 – Data available to make classification

**Other information**

Not Available

**SECTION 12 Ecological information****Toxicity**

|   | Endpoint   | Test Duration (hr) | Species       | Value         | Source        |
|---|--|--------------------|---------------|---------------|---------------|
| GulfSea BD Hydraulic Oil 32, 46, 68, 100                            | Not Available  | Not Available      | Not Available | Not Available | Not Available |
| 7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated | Not Available  | Not Available      | Not Available | Not Available | Not Available |
| <b>Legend:</b>  | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data |                    |               |               |               |

**DO NOT** discharge into sewer or waterways.**Persistence and degradability**

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

**Bioaccumulative potential**

| Ingredient | Bioaccumulation                       |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

**Mobility in soil**

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

**Other adverse effects**

No evidence of ozone depleting properties were found in the current literature.

**SECTION 13 Disposal considerations****Waste treatment methods**

|                                     |   |
|-------------------------------------|---|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> |
|-------------------------------------|---|

**SECTION 14 Transport information****Labels Required**

|                         |    |
|-------------------------|----|
| <b>Marine Pollutant</b> | NO |
|-------------------------|----|

**Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****14.7. Maritime transport in bulk according to IMO instruments****14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

Continued...

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name  | Group          |
|---|----------------|
| 7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated | Not Applicable |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name  | Ship Type      |
|---|----------------|
| 7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated | Not Applicable |

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture**

7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated is found on the following regulatory lists

Not Applicable

**Additional Regulatory Information**

Not Applicable

**National Inventory Status**

| National Inventory                                | Status  |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use   | Yes   |
| Canada - DSL                                      | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Canada - NDSL                                     | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| China - IECSC                                     | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Europe - EINEC / ELINCS / NLP                     | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Japan - ENCS                                      | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Korea - KECI                                      | Yes   |
| New Zealand - NZIoC                               | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Philippines - PICCS                               | Yes   |
| USA - TSCA  | All chemical substances in this product have been designated as TSCA Inventory 'Active'   |
| Taiwan - TCSI                                     | Yes   |
| Mexico - INSQ                                     | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| Vietnam - NCI                                     | Yes   |
| Russia - FBEPH                                    | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| UAE - Control List (Banned/Restricted Substances) | No (7-methylenepentadecene, 1-tetradecene dimers, trimers, hydrogenated)  |
| <b>Legend:</b>                                    | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

**SECTION 16 Other information**

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 27/09/2023 |
| <b>Initial Date</b>  | 14/08/2023 |

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.