



PRODUCT DATA SHEET

GulfSea ATF III

High performance Automatic Transmission Fluid

Product Description

GulfSea ATF III is a high performance automatic transmission fluid for all General Motors and Ford automatic transmissions requiring DEXRON®-III G or MERCON® quality fluids respectively. The specially selected performance additives and base oils in this oil proved improved thermo-oxidative stability, friction retention properties, corrosion & rust protection, foam control and seal compatibility. It exceeds the performance requirements of General Motors DEXRON® III G and Ford MERCON® specifications.

Features & Benefits

- Improved thermo-oxidative stability, wear protection and resistance to chemical deterioration protect against degradation at high operating temperatures and helps in maintaining the efficiency of the transmission system.
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.
- Controlled frictional properties provide smooth transmission and good shift performance.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Provides improved protection against rust and corrosion.
- Superior Low temperature pumpability and circulation ensures good cold start performance.
- Compatibility with all common seal materials reduces possibility of oil leakage.

Applications

- Recommended for all vehicles of Ford requiring MERCON® quality fluids and General Motors requiring DEXRON®-III G quality fluids.
- Being back serviceable, it is also recommended for automatic transmissions requiring General Motors DEXRON® II E or DEXRON® II D fluids.
- Also recommended for power steering systems, hydraulic applications and certain manual transmissions where such type of fluids are specified.

Typical Properties

| GulfSea ATF III | | |
|--|-------------|-------------|
| Meets the following Specification | | |
| Former General Motors DEXRON® III G | | |
| Former Ford MERCON® | | |
| Typical Properties | | |
| Test Parameters | ASTM Method | Test Values |
| Viscosity @ 100 °C, cSt | D 445 | 7.9 |
| Viscosity Index | D 2270 | 168 |
| Flash Point, °C | D 92 | 184 |
| Pour Point, °C | D 97 | -40 |
| Brookfield Viscosity @ -40 0C, cP | D 2983 | 17900 |
| Density @ 15°C, Kg/l | D 1298 | 0.827 |

March 2026

Due to continual product research and development, the information contain herein is subject to change without notification.
Typical Properties may vary slightly