



GulfSea Synth LPG Compressor Oil

Gulf Marine Pte. Ltd.

Chemwatch: 9037-14

Version No: 2.1

Safety Data Sheet in accordance with SS 586-3:2022

Initial Date: 29/06/2026

Revision Date: 29/06/2026

Print Date: 28/07/2026

S.GHS.SGP.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	GulfSea Synth LPG Compressor Oil
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	2SC51500-82

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Compressor Oil Use according to manufacturer's directions.
--------------------------	---

Details of the manufacturer or importer of the safety data sheet

Registered company name	Gulf Marine Pte. Ltd.
Address	37 Tuas Road 638503 Singapore
Telephone	+65 6592 0120
Fax	Not Available
Website	Not Available
Email	sds@gulf-marine.com

Emergency telephone number

Association / Organisation	Gulf Marine Pte. Ltd.
Emergency telephone number(s)	+65 6592 0120
Other emergency telephone number(s)	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification	Serious Eye Damage/Eye Irritation Category 1
----------------	--

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H318	Causes serious eye damage.
------	----------------------------

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
------	--

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

Other hazards

- Ingestion may produce health damage*.
- Possible skin sensitizer*.
- Repeated exposure potentially causes skin dryness and cracking*.

*LIMITED EVIDENCE

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	Synonyms	Chemical formula
9038-95-3	<60	<u>butyl alcohol</u> <u>propoxylated</u>	C4 H10 O.(C3 H6 O.C2 H4 O)x; butyl ether propoxylated; 1-[2-[2-(3-methoxypropoxy)propoxy]ethoxy]butane (9:10); 2-(1-butoxypropan-2-yloxy)ethanol; PPG-10-buteth-9; oxirane, methyl-, polymer with oxirane, butyl ether; PPG-26-buteth-26; butyl polyoxyalkylene ethers; butyl PPG ethers; butyl PPG/PEG ethers; Buteth-3 (polyethylene glycol ether of butyl alcohol) CAS RN: 143 -22-6	C10H22O4[C13H28O4] (C3H6O)nC4H10O[C4H10O. (C3H6O.C2H4O)x

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
---------------	---

Continued...

GulfSea Synth LPG Compressor Oil

	▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ Avoid spraying water onto liquid pools. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). ▶ May emit acrid smoke. ▶ Mists containing combustible materials may be explosive. Combustion products include: ▶ carbon dioxide (CO₂) ▶ other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Wipe up. ▶ Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ No smoking, naked lights or ignition sources. ▶ Increase ventilation. ▶ Stop leak if safe to do so. ▶ Contain spill with sand, earth or vermiculite. ▶ Collect recoverable product into labelled containers for recycling. ▶ Absorb remaining product with sand, earth or vermiculite. ▶ Collect solid residues and seal in labelled drums for disposal. ▶ Wash area and prevent runoff into drains. ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Overheating of ethoxylates/ alkoxyates in air should be avoided. When some ethoxylates are heated vigorously in the presence of air or oxygen, at temperatures exceeding 160 C, they may undergo exothermic oxidative degeneration resulting in self-heating and autoignition. ▶ Nitrogen blanketing will minimise the potential for ethoxylate oxidation. Prolonged storage in the presence of air or oxygen may cause product degradation. Oxidation is not expected when stored under a nitrogen atmosphere. Inert gas blanket and breathing system needed to maintain color stability. Use dry inert gas having at least -40 C dew point. ▶ Trace quantities of ethylene oxide may be present in the material. Although these may accumulate in the headspace of storage and transport vessels, concentrations are not expected to exceed levels which might produce a flammability or worker exposure hazard. ▶ Avoid skin contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Continued...

Conditions for safe storage, including any incompatibilities

Suitable container	For ethoxylates suitable containers include carbon steel coated with baked phenolic. Any moisture may cause rusting of carbon steel. If product is moisture free, uncoated carbon steel tanks may be used. ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. <table><tr><td>Type of Contaminant:</td><td>Air Speed:</td></tr><tr><td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td><td>0.25-0.5 m/s (50-100 f/min)</td></tr><tr><td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s (100-200 f/min.)</td></tr><tr><td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min)</td></tr><tr><td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td><td>2.5-10 m/s (500-2000 f/min.)</td></tr></table> Within each range the appropriate value depends on: <table><tr><td>Lower end of the range</td><td>Upper end of the range</td></tr><tr><td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr><tr><td>2: Contaminants of low toxicity or of nuisance value only</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood - local control only</td></tr></table> Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood - local control only
Type of Contaminant:	Air Speed:																				
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)																				
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)																				
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)																				
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)																				
Lower end of the range	Upper end of the range																				
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																				
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity																				
3: Intermittent, low production.	3: High production, heavy use																				
4: Large hood or large air mass in motion	4: Small hood - local control only																				
Individual protection measures, such as personal protective equipment																					
Eye and face protection	▶ Safety glasses with side shields. ▶ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].																				
Skin protection	See Hand protection below																				
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.																				

GulfSea Synth LPG Compressor Oil

	Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream. ▶ Skin cleansing cream. ▶ Eye wash unit.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Clear to slightly yellow liquid with petroleum odor; mixes with water		
Physical state	Liquid	Relative density (Water = 1)	1.035-1.065
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	68-320 at 40°C
Initial boiling point and boiling range (°C)	>392	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>=236	Taste	Not Available

Continued...

Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	>1	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	- Unstable in the presence of incompatible materials. - Product is considered stable. - Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Nonionic surfactants may produce localised irritation of the oral or gastrointestinal lining and induce vomiting and mild diarrhoea.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Non-ionic surfactants cause less irritation than other surfactants as they have less ability to denature protein in the skin. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage. Non-ionic surfactants can cause numbing of the cornea, which masks discomfort normally caused by other agents and leads to corneal injury. Irritation varies depending on the duration of contact, the nature and concentration of the surfactant.
Chronic	There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation.

GulfSea Synth LPG Compressor Oil	TOXICITY	IRRITATION
	Not Available	Not Available

butyl alcohol propoxylated	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 13340 mg/kg ^[2]	Eye (Rodent - rabbit): 20mg/24H - Moderate
	Inhalation (Rat) LC50: 0.147 mg/L4h ^[2]	Eye (Rodent - rabbit): 500mg
	Oral (Rabbit) LD50; 1770 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg
		Eye (Rodent - rabbit): 500mg/24H - Mild
		Eye (Rodent - rabbit): 500mg/24H - Mild
		Eye (Rodent - rabbit): 50mg - Severe
		Eye (Rodent - rabbit): 50mg - Severe
		Eye: adverse effect observed (irritating) ^[1]
		Eye: no adverse effect observed (not irritating) ^[1]
		Skin (Rodent - rabbit): 10mg/24H - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg - Mild
		Skin (Rodent - rabbit): 500mg/24H - Mild
		Skin (Rodent - rabbit): 500mg/24H - Mild
		Skin (Rodent - rabbit): 500mg/24H - Mild
		Skin (Rodent - rabbit): 80mg/4H
		Skin (Rodent - rabbit): 80mg/4H - Mild
		Skin: adverse effect observed (irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

BUTYL ALCOHOL PROPOXYLATED	In general, the toxicity of the PPGs Butyl Ether decreased with increasing molecular weight; for example, PPG-40 Butyl Ether was less toxic than PPG-2 Butyl Ether. Mutagenicity data were not found on the PPGs Butyl Ether. However, an ether of molecular weight 800 Da (~PPG-13 Butyl Ether) was non-carcinogenic when fed to rats for 2 years. Because the PPGs Butyl Ethers undergo metabolic degradation; i.e., the butyl group are removed and oxidized, the PPG chains are split into random length fragments, the genotoxicity of the component chemicals, propylene glycol (PG) and n- Butyl Alcohol, were also considered. Both PG and n-Butyl Alcohol were non-mutagenic in mammalian and microbial assays. PG was non-carcinogenic in a 2-year feeding study using rats and in a lifetime dermal study using mice. These studies effectively eliminated the need for genotoxicity data on the PPG Butyl Ethers. There was concern about the irritancy potential of PPG-2 Butyl Ether. In animal irritation studies, the ingredient caused minor, transient erythema and desquamation; in addition, erythema, edema, ecchymosis, necrosis, and other changes were observed during an acute percutaneous study. PPG-2 Butyl Ether also caused minor to moderate conjunctival irritation and minor corneal injury. It was concluded that the PPG Butyl Ethers were safe for use in cosmetics when formulated to avoid irritation. The dermal LD50 of PPG-3 Butyl Ether was 2 g/kg in rats and rabbits, and the dermal LD50 of Buteth-3 in rats was 3.5 g/kg. The oral LD50 of PPG-3 Butyl Ether and of Buteth-3 in rats was 2 g/kg and 6.6 g/kg, respectively. Polypropyleneglycol butyl ethers (not defined) had a dermal and an oral LD50 of 2 g/kg and 0.3-2 g/kg bw, respectively,in mice.Buteth-3 (1000 mg/kg/day) was not toxic to rabbits in a 21-day dermal study; erythema, desquamation, and fissuring were observed in short-term oral toxicity studies in rats, PPG-3 Butyl Ether had a NOAEL of 1000 mg/kg bw; polypropylene glycol butyl ethers had a NOEL of 100 mg/kg bw/day for clinical observations, higher absolute and relative liver weights, and an increased incidence of liver and thyroid gland hypertrophy; and 1-(2-butoxy-1-methylethoxy)propan-2-ol had a NOAEL of 100 mg/kg/day based on very slight to slight hepatocellular hypertrophy with no corresponding increases in liver weights in low-dose males. In a 90-day oral toxicity study, administration of up to 1000 mg/kg bw/day PPG-3 Butyl Ether to rats in drinking water produced treatment-related increases in absolute and relative liver and kidney weights. The NOAELs in rats and mice exposed to=3000 ppm methoxyisopropanol via inhalation for 2 yrs were 1000 ppm (based on slight body wt decreases in males and females) and 300 ppm (based on altered hepatocellular foci in males), respectively.Dermal application of propylene glycol butyl ether was not embryotoxic or teratogenic to rabbits (=100 mg/kg bw/day applied on days 7-18 of gestation) or rats (=1.0 ml/kg bw/day applied on days 6-16 of gestation). 1-(2-Butoxy-1-methyl-ethoxy)propan-2-ol (applied on days 6-16 or 6-15 of gestation) also was not embryotoxic or teratogenic in rats. No test-article related adverse developmental or reproductive effects were observed in rats dosed by gavage with up to 1000 mg/kg Buteth-3 or 1-(2-butoxy-1-methylethoxy)propan-2-ol or up to 500 mg/kg bw/day polypropylene glycol butyl ethers. In inhalation studies, exposure of rats to =1.0 mg/l air PPG-3 Methyl Ether did not have any teratogenic or reproductive effects. Exposure to 1000 and 3000 ppm methoxyisopropanol produced some adverse effects in a two-generation study in rats; adverse effects were not observed with 300 ppm. PPG-3 Butyl Ether was not genotoxic in vitro in the Ames test or in vivo in a mouse micronucleus assay. Propylene glycol butyl ether was not genotoxic in an Ames test or a mammalian chromosomal aberration assay in rat lymphocytes, andneither propylene glycol butyl ether or 1-(2-butoxy-1-methylethoxy)propan-2-ol were genotoxic in a mammalian cellmutation assay in CHO cell. In inhalation carcinogenicity studies, mice and rats were exposed by whole body exposure to =3000 ppm methoxyisopropan-ol for 2 yrs. An increase in S-phase DNA synthesis and in MFO activity in the liver was observed in high-dose male mice and rats. Renal epithelial tumors were not observed, and the NOEL for carcinogenicity was 3000 ppm for mice and rats. Undiluted PPG-3 Butyl Ether was not irritating to rabbit skin or eyes, and it was not an irritant or sensitizer in guinea pigs. Polypropylene glycol butyl ethers were classified as non-corrosive in an EpiDermTM study Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products. Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation.
----------------------------	--

Humans have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents and other cleaning products. Exposure to these chemicals can occur through swallowing, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that relatively high volumes would have to occur to produce any toxic response. No death due to poisoning with alcohol ethoxylates has ever been reported. Studies show that alcohol ethoxylates have low toxicity through swallowing and skin contact. Animal studies show these chemicals may produce gastrointestinal irritation, stomach ulcers, hair standing up, diarrhea and lethargy. Slight to severe irritation occurred when undiluted alcohol ethoxylates were applied to the skin and eyes of animals. These chemicals show no indication of genetic toxicity or potential to cause mutations and cancers. Toxicity is thought to be substantially lower than that of nonylphenol ethoxylates.

Some of the oxidation products of this group of substances may have sensitizing properties.

As they cause less irritation, nonionic surfactants are often preferred to ionic surfactants in topical products. However, their tendency to auto-oxidise also increases their irritation. Due to their irritating effect it is difficult to diagnose allergic contact dermatitis (ACD) by patch testing. Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No adverse reproductive or developmental effects were observed.

Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma. Death may result in experimental animal. However, repeated exposure may cause dose dependent damage to the kidneys as well as reproductive and developmental defects.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

Other information
Not Available

SECTION 12 Ecological information

Butyl alcohol propoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
butyl alcohol propoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>500mg/l	1
	EC50	48h	Crustacea	>500mg/l	1
	NOEC(ECx)	72h	Algae or other aquatic plants	62.5mg/l	2
	EC50	96h	Algae or other aquatic plants	744.74mg/l	2
	LC50	96h	Fish	1350mg/l	1
	EC50	72h	Algae or other aquatic plants	445mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
	EC50	96h	Algae or other aquatic plants	315mg/l	2
	NOEC(ECx)	96h	Algae or other aquatic plants	<15.9mg/l	2
	LC50	96h	Fish	564mg/l	2
	EC50	48h	Crustacea	89-101mg/L	4
	EC50(ECx)	48h	Crustacea	89-101mg/L	4
	LC50	96h	Fish	48-52mg/L	4
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For High Boiling Point Ethylene Glycol Ethers: Koc: 10; log Kow: -1.73 to +0.51 @ 20 C. Henry's Law Constant: 3.54 E-14 to 3.67 E-13 m3 atm/mol @ 25 C. These chemicals form a category based on similar structural, physiochemical and toxicological properties. Triethylene- and tetraethylene- glycol ethers represent typical members of the category.

Environmental Fate: All have high boiling points, low volatility and high water solubility. Higher molecular weight species and surrogates may be solids at ambient temperatures.

Atmospheric Fate: Triethylene glycol butyl ether (TGBE), tetraethylene glycol methyl ether (TetraME) and tetraethylene glycol butyl ether (TetraBE) have atmospheric photodegradation half-lives of 2.5, 2.4 and 2.0 hours, respectively.

Terrestrial Fate: High boiling point ethylene glycol ethers have uniformly high soil mobility thus, leaching of these products from soil deposits to groundwater can be expected as well as transportation to environments where aerobic biodegradation can take place. Triethylene glycol methyl ether (TGME), triethylene glycol ethyl ether (TGEE) and triethylene glycol butyl ether (TGBE) showed slower rates of biodegradation. Studies have shown variable results for the tri- and tetraethylene glycol ethers.

Aquatic Fate: Ether groups are generally stable to water under neutral conditions and ambient temperatures. The category members are highly soluble to miscible in water and tend to stay dissolved. Biodegradation of category members is reasonably rapid.

Ecotoxicity: None of the category members showed limited biodegradation or bioaccumulation potential. Trimethyl-, -ethyl and -butyl ethers and are practically non-toxic to aquatic species. No major differences are observed in the order of toxicity going from the methyl- to the butyl ethers. TetraME and TetraBE are likely to have low toxicity to aquatic species. Trimethyl-, -ethyl and -butyl ethers are not acutely toxic to Daphnia magna water fleas, fish or algae.

For Alcohol Ethoxylates (AE):

Environmental Fate: AEs are commonly found in surfactants, are generally biodegradable, and do not persist for any substantial period in the environment. They are not usually present at concentrations which might produce problems.

Terrestrial Fate: The adsorption of AEs in soil decreases as pH increases. These substances will be broken down by microorganisms in the presence of oxygen.

Breakdown in the Environment (Biodegradation): AE with a typical alkyl chain, (e.g., C12 to C15), will normally reach more than 60% degradation in standardized tests for ready biodegradability. However, the presence of longer chain ethylene oxide components may reduce the ability of microorganisms to break the substance down. Branched AEs degrade slower than linear AEs. These substances are rapidly degraded by oxygen dependent microorganisms. Octyl- and nonyl- phenol ethoxylates are not readily biodegradable but are inherently biodegradable.

Aquatic Fate: Contamination of natural waters by AEs should be avoided. The linear AEs are normally easily degraded in oxygenated waters.

Ecotoxicity: Alcohol ethoxylates can have acute and chronic toxic effects toward aquatic organisms. Toxicity generally declines as the number of ethoxylates increases. The effects of alcohol ethoxylates on aquatic species include reduced growth rates, impaired reproduction, reduced survival of neonates, as well as acute mortality. Alcohol ethoxylates may cause diminished growth rate/reduced cell counts in algae species, at very low concentrations. Algae are the most sensitive group to AE. The toxicity of AE to algae tends to decrease with increasing degree of branching of the substances. Alcohol ethoxylates degrade more quickly in the aquatic environment to relatively non-toxic compounds. Nonylphenol ethoxylate degradation typically yields nonylphenol, which is toxic, as well as persistent, in the aquatic environment. The acute toxicity of AE to invertebrates varies from toxic to moderately toxic, for both linear and branched types. Daphnia magna and pulex are the most sensitive invertebrates to AEs. Some AEs are very toxic to invertebrates. AEs are generally very toxic to fish.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
butyl alcohol propoxylated	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
butyl alcohol propoxylated	LOW (LogKOW = 1.2706)

Mobility in soil

Ingredient	Mobility
butyl alcohol propoxylated	LOW (Log KOC = 10)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Authority for disposal. ▶ Bury or incinerate residue at an approved site. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	--

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
------------------	----

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
butyl alcohol propoxylated	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
butyl alcohol propoxylated	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

butyl alcohol propoxylated is found on the following regulatory lists
Not Applicable

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (butyl alcohol propoxylated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (butyl alcohol propoxylated)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	29/06/2026
Initial Date	29/06/2026

Other information

Ingredients with multiple cas numbers

Name	CAS No
butyl alcohol propoxylated	9065-63-8, 1033553-65-9, 9038-95-3, 9003-13-8, 55934-93-5, 143-22-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.